



POWERED BY MAMMOTH

BUNDED ROUND TANK



STANDARD SIZES

ECOBND5000P

Bunded Round Poly Tank: 5,000L
2,750(L) X 2,200(W) X 2,260(H)

ECOBND7000P

Bunded Round Poly Tank: 7,000L
3,070(L) x 2,500(W) x 2,350(H)

ECOBND10000P

Bunded Round Poly Tank: 10,000L
3,062(L) x 2,500(W) x 2,710(H)

*Average dimensions listed as regulations vary per location

PAD REQUIREMENTS

- 150mm thick level surface
- Pad width to extend a metre around the footprint of the tank
- Footprint requires to be free of any debris, rocks, or vegetation
- Concrete pad or blue metal aggregate to extend 500mm beyond the tank footprint



STANDARD FEATURES

- Lockable Cabinet
- 240V Transfer Pump (30 LPM) + Electrical Box
- 50mm stainless steel fill point Dry Break Fitting
- Overfill Protection Valve
- OCIO level indication Gauge
- Hi-Level alarm
- 5m hose, auto nozzle, nozzle holster
- Digital flow meter
- ECODIP Telemetry

OPTIONAL EXTRAS

- Submersible Pump (for External Bowser)
- High Flow Dispensing (150 LPM)
- Solar Power Supply
- External Nozzle Boot
- Standard Height Hose Mast (2m)
- High Hose Mast (6m)
- Hose reel
- MC Box and user key or pin code fob system
- Fuel management integration



1300 272 444
orders@ecoblue.com